



3-D prism laser with 1 green horizontal line all round and 2 vertical lines all round (= plumb line above and below + 4 angles of 90°). Pendulum levelling accurate to 2 mm/10 m. Comes with multifunctional magnetic wall mount. Li-Ion battery with AC adapter/charger.

Main specifications

Visibility	
Precision	2mm / 10m
Range (with receiver)	2x 150m
Dust- and water resistance	IP54
Batteries	LI-ION (2x)
AC power connector	✓
Levelling	Pendulum levelling

Power supply and batteries

Batteries	7.4V 2600mAh Li-ion
AC power connector	✓
Charger integrated into AC power connector	✓
Life (with all diodes on)	± 8h
DxWxH device	135 x 85 x 110 mm
Weight of device	0,59 kg
DxWxH box	155 x 420 x 350 mm
Weight box	3,95 kg

Detailed specifications

Plumb bob	✓
Number of laser dots per line	0
Number of 90° angles	4
Number of 45° angles	0
Rotations per minute	Not applicable
Scan function	✗
Wind function	✗
Tilt function	✗
Self-levelling range	±4°
Slope function	Manual
Maximum settable slope (X-axis/Y-axis)	+/- 45°
Remote control	✓
Built-in screw for tripod	1/4
Pendulum lock (for manual slopes)	✓
Transport security for the pendulum	✓
Number of laser diodes	3
Laser frequency (in receiver mode)	10KHz
Laser class	Class 2 - 520NM - <1mW
Dust and water tightness	IP54

IN THE BOX



035.3DG



HCASE.3DC



180.20



180.40



130.08



H035.TUR



H60027



H60028

ACCESSORIES

Tripods



091.150

Tripod Light Duty 150cm
- Tilting head - 1/4



130.10

Mini tripod with shifting
base for 3D Crosslasers

Receivers



150.12.LT

Line Tracer Red/Green



150.40.A

Quattro



150.40.M

Quattro MM

Adapters, chargers and batteries



H60027

Charger MC3D Compact
Li-ion



H60028

Li-Ion Battery 7.4V
2600mAh