


EUROGROOVE

CE1820EGR



ITEM SIZE (mm)

17,8 x 20

GROOVE SIZE (mm)

17,9 x 20

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL H. Sound-insulating seal in self-extinguishing thermoplastic. Color: Grey.

CLOSING END-CAP Not included

ACTIVATION PLUNGER 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench. Nylon PA6 30% Fiberglass reinforced. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -20° / + 80°

FIXING TYPE 3F. with screws on pre-holed seal (screws not included).

CERTIFICATES

WORKING CYCLES 200.000 (internal test)

ACOUSTIC INSULATION /

FIRE RESISTANCE /

SMOKE TESTED /

EUROGROOVE

CE1820EGR

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,115	6,60	50	330 -> 280
430	0,149	8,30	150	430 -> 280
530	0,183	10,00	150	530 -> 380
630	0,217	11,70	150	630 -> 480
730	0,251	13,40	150	730 -> 580
830	0,285	15,10	150	830 -> 680
930	0,319	16,80	150	930 -> 780
1030	0,353	18,50	150	1030 -> 880
1130	0,387	20,20	150	1130 -> 980
1230	0,421	21,90	150	1230 -> 1080
1330	/	/	/	/
1430	/	/	/	/
1530	/	/	/	/
1630	/	/	/	/
1730	/	/	/	/
1830	/	/	/	/

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 50 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.