


ALU PLUS

CE1718APL



ITEM SIZE (mm)

16,6 x 18

GROOVE SIZE (mm)

16,7 x 18

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL I. Sound-insulating seal in self-extinguishing thermoplastic. Color: Grey.

CLOSING END-CAP Not included

ACTIVATION PLUNGER 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench.
Nylon PA6 30% Fiberglass reinforced. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -20° / +80°

FIXING TYPE 3F. with screws on pre-holed seal (screws not included).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION **46dB Rw** - Cert. n. 167-3827/Z12e - IFT Rosenheim

FIRE RESISTANCE **60 mins** - Cert. n. 20/22763-1241-1 - Applus Laboratories

SMOKE TESTED /

ALU PLUS

CE1718APL

ITEM LENGTH mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,102	5,95	50	330 -> 280
430	0,132	7,45	150	430 -> 280
530	0,162	8,95	150	530 -> 380
630	0,192	10,45	150	630 -> 480
730	0,222	11,95	150	730 -> 580
830	0,252	13,45	150	830 -> 680
930	0,282	14,95	150	930 -> 780
1030	0,312	16,45	150	1030 -> 880
1130	0,342	17,95	150	1130 -> 980
1230	0,372	19,45	150	1230 -> 1080

PACKAGING

- MINIMUM PACKAGING 5 pieces
- BOX PACKAGING 50 pieces

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.
Keep stored in a dry place, protected from water, solvents and direct sunlight.

