


CHRONOSOFT 15x30

CE1530CHR



ITEM SIZE (mm)

15 x 30

GROOVE SIZE (mm)

15,1 x 30

AVAILABLE LENGTHS (mm)

330* - 430* - 530* - 630 - 730 - 830 - 930 - 1030 -
1130 - 1230 - 1330 - 1430 - 1530

*without hydraulic delay

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced + metallic hydraulic piston d.12 mm

SEAL RT5. Self extinguishing silicone UL94 V0. Color: grey

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: grey

ACTIVATION PLUNGER Extractable nylon plunger with round head with manual adjustability.
Nylon PA6 30% Fiberglass reinforced. Color: grey.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 12

WORKING TEMPERATURES (C°) -20° / + 80°

FIXING TYPE 1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws) or
3F. removing the inner profile (screws not included).

CERTIFICATES

WORKING CYCLES 200.000 (internal test)

ACOUSTIC INSULATION **51,5dB Rw** - Cert. n. PB-Z04-K06-04-en-01 - IFT Rosenheim

FIRE RESISTANCE **120 mins** - Cert. n. 20/22763-1240-1 - Applus Laboratories

FIRE RESISTANCE **60 mins** - File n. R39141 - UL Underwriters Laboratories

SMOKE TESTED /

CHRONOSOFT 15x30

CE1530CHR

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,17	5,95	50	330 -> 280
430	0,22	7,45	135	430 -> 295
530	0,27	8,95	150	530 -> 380
630	0,32	10,45	125	630 -> 505
730	0,37	11,95	150	730 -> 580
830	0,42	13,45	150	830 -> 680
930	0,47	14,95	150	930 -> 780
1030	0,52	16,95	150	1030 -> 880
1130	0,57	17,95	150	1130 -> 980
1230	0,62	19,45	150	1230 -> 1080
1330	0,67	20,95	150	1330 -> 1180
1430	0,72	/	150	1430 -> 1280
1530	0,77	/	150	1530 -> 1380
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/

PACKAGING

MINIMUM PACKAGING 1 piece in nylon bag

BOX PACKAGING 30 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.