


DECIBEL

CE2030DCB



ITEM SIZE (mm)

20 x 30

GROOVE SIZE (mm)

20,1 x 30

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL E. Sound-insulating seal in self-extinguishing thermoplastic. Color: black

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black

ACTIVATION PLUNGER 7D. Double plunger with striker plates supplied as standard. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -35° / + 200°

FIXING TYPE 3F. removing the inner profile (screws not included).

CERTIFICATES

WORKING CYCLES 200.000 (internal test)

ACOUSTIC INSULATION **52dB** Rw - Cert. n. PB-G03-04-en-01-PB04 - IFT Rosenheim

FIRE RESISTANCE /

SMOKE TESTED /

DECIBEL

CE2030DCB

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,247	6,870	50	330 -> 280
430	0,322	8,750	110	430 -> 320
530	0,397	10,620	110	530 -> 420
630	0,472	12,500	110	630 -> 520
730	0,547	14,170	110	730 -> 620
830	0,622	16,250	110	830 -> 720
930	0,697	18,120	110	930 -> 820
1030	0,772	20,000	110	1030 -> 920
1130	0,847	21,870	110	1130 -> 1020
1230	0,922	23,750	110	1230 -> 1120
1330	/	/	/	/
1430	/	/	/	/
1530	/	/	/	/
1630	/	/	/	/
1730	/	/	/	/
1830	/	/	/	/

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 25 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.