


CON GUARNIZIONE SFILABILE 12x30

CE1230GSF



ITEM SIZE (mm)

11,7 x 30

GROOVE SIZE (mm)

11,8 x 30

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 -
1230 - 1330 - 1430 - 1530 - 1630 - 1730 - 1830

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL B. Balloon in self-extinguishing silicone UL94-V0.

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black.

ACTIVATION PLUNGER 1. Self-directing articulated metal plunger with nylon cap, adjustable with a 3 mm Allen wrench.
Colour: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -35° / + 200°

FIXING TYPE 2F. With premounted screws (3,5x20 countersunk nickel plated screws) or

3F. removing the inner profile (screws not included).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION **44dB Rw** - Cert. n. PB-G03-04-en-01_PB11 - IFT Rosenheim

FIRE RESISTANCE /

SMOKE TESTED /

CON GUARNIZIONE SFILABILE 12x30

CE1230GSF

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,130	7,20	50	330 -> 280
430	0,170	9,20	135	430 -> 295
530	0,210	11,20	200	530 -> 330
630	0,250	13,20	200	630 -> 430
730	0,290	15,20	200	730 -> 530
830	0,330	17,20	200	830 -> 630
930	0,370	19,20	200	930 -> 730
1030	0,410	21,20	200	1030 -> 830
1130	0,450	23,20	200	1130 -> 930
1230	0,490	25,20	200	1230 -> 1030
1330	0,530	27,20	200	1330 -> 1130
1430	0,570	/	200	1430 -> 1230
1530	0,610	/	200	1530 -> 1330
1630	0,650	/	200	1630 -> 1430
1730	0,690	/	200	1730 -> 1530
1830	0,730	/	200	1830 -> 1630

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 50 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.

