


SMALL

CE1213SML

**ITEM SIZE (mm)**

11,7 x 12,5

GROOVE SIZE (mm)

11,8 x 12,5

AVAILABLE LENGHTS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL B. Balloon in self-extinguishing silicone UL94-V0.

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black.

ACTIVATION PLUNGER 1. Self-directing articulated metal plunger with nylon cap, adjustable with a 3 mm Allen wrench.
Colour: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 10

WORKING TEMPERATURES (C°) -35° / + 200°

FIXING TYPE 3F. removing the inner profile (screws not included).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION /

FIRE RESISTANCE /

SMOKE TESTED /

SMALL

CE1213SML

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,076	8,30	35	330 -> 295
430	0,098	10,05	120	430 -> 310
530	0,120	12,70	150	530 -> 380
630	0,142	14,90	150	630 -> 480
730	0,164	17,10	150	730 -> 580
830	0,186	19,30	150	830 -> 680
930	0,208	21,50	150	930 -> 780
1030	0,230	23,70	150	1030 -> 880
1130	0,252	25,90	150	1130 -> 980
1230	0,274	28,10	150	1230 -> 1080
1330	/	/	/	/
1430	/	/	/	/
1530	/	/	/	/
1630	/	/	/	/
1730	/	/	/	/
1830	/	/	/	/

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 100 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.