


12x40 SQUADRETTE

CE1240GSQ

**ITEM SIZE (mm)**

12 x 40

GROOVE SIZE (mm)

12,1 x 40

AVAILABLE LENGHTS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 -
1230 - 1330 - 1430 - 1530 - 1630 - 1730 - 1830

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL SQ. Self extinguishing silicone UL94 class V0. Color: grey

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black.

ACTIVATION PLUNGER 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench.
Nylon PA6 30% Fiberglass reinforced. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -35° / + 200°

FIXING TYPE 1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION /

FIRE RESISTANCE /

SMOKE TESTED /

12x40 SQUADRETTE

CE1240GSQ

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,159	5,47	50	330 -> 280
430	0,207	6,91	135	430 -> 295
530	0,255	8,35	200	530 -> 330
630	0,303	9,79	200	630 -> 430
730	0,351	11,23	200	730 -> 530
830	0,399	12,67	200	830 -> 630
930	0,477	14,11	200	930 -> 730
1030	0,495	15,55	200	1030 -> 830
1130	0,543	16,99	200	1130 -> 930
1230	0,591	18,43	200	1230 -> 1030
1330	0,639	19,87	200	1330 -> 1130
1430	0,687	/	200	1430 -> 1230
1530	0,735	/	200	1530 -> 1330
1630	0,783	/	200	1630 -> 1430
1730	0,831	/	200	1730 -> 1530
1830	0,879	/	200	1830 -> 1630

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 30 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.