


TREND PLUS

CE1320TDP



ITEM SIZE (mm)

12,8 x 20

GROOVE SIZE (mm)

12,9 x 20

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL H. Self extinguishing thermoplastic. Color: grey

CLOSING END-CAP Included.

ACTIVATION PLUNGER 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench. Nylon PA6 30% Fiberglass reinforced. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -35° / + 200°

FIXING TYPE 3F. With pre-holed seal for screw fitting

CERTIFICATES

WORKING CYCLES 200.000 (internal test)

ACOUSTIC INSULATION **50dB Rw** - Cert. n. PB06-Z10-G03-04-en-01 - IFT Rosenheim

FIRE RESISTANCE /

SMOKE TESTED /

TREND PLUS

CE1320TDP

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,114	7,590	50	330 -> 260
430	0,149	9,690	135	430 -> 295
530	0,184	11,790	150	530 -> 380
630	0,219	13,890	150	630 -> 480
730	0,254	15,990	150	730 -> 580
830	0,289	18,900	150	830 -> 680
930	0,324	20,190	150	930 -> 780
1030	0,359	22,290	150	1030 -> 880
1130	0,394	24,390	150	1130 -> 980
1230	0,429	26,490	150	1230 -> 1080
1330	/	/	/	/
1430	/	/	/	/
1530	/	/	/	/
1630	/	/	/	/
1730	/	/	/	/
1830	/	/	/	/

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 60 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.

