


ACOUSTIC ALU EUROGROOVE

ASACAGR-GA-14



ITEM SIZE (mm)

25 x 20

GROOVE SIZE (mm)

25,1 x 20

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 -
1230 - 1330 - 1430 - 1530

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL GA. Sound-insulating seal in self-extinguishing thermoplastic. Color: Grey.

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black

ACTIVATION PLUNGER 16. Nylon plunger with rounded head adjustable with a 3 mm Allen wrench. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (C°) -20° / +80°

FIXING TYPE 2F. With screws (3,5x30 pan head (wood) or
3,5x32 (steel) countersunk nickel plated screws) on pre-holed seal or
1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION **50dB Rw** - Cert. n. PB-G03-04-en-01-PB01 - IFT Rosenheim

FIRE RESISTANCE /

SMOKE TESTED /



ACOUSTIC ALU EUROGROOVE

ASACAGR-GA-14

ITEM LENGTH mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,160	5,65	50	330 -> 280
430	0,210	7,15	110	430 -> 320
530	0,260	8,65	150	530 -> 380
630	0,310	10,15	150	630 -> 480
730	0,360	11,65	150	730 -> 580
830	0,410	13,15	150	830 -> 680
930	0,460	14,65	150	930 -> 780
1030	0,510	16,15	150	1030 -> 880
1130	0,560	17,65	150	1130 -> 980
1230	0,610	19,15	150	1230 -> 1080
1330	0,660	20,65	150	1330 -> 1180
1430	0,710	21,65	150	1430 -> 1280
1530	0,760	23,15	150	1530 -> 1380

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 30 pieces

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.

