


ACOUSTIC ALU

CE2520ACA



ITEM SIZE (mm)

25 x 20

GROOVE SIZE (mm)

25,1 x 20

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 -
1230 - 1330 - 1430 - 1530

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL GA. Sound-insulating seal in self-extinguishing thermoplastic. Color: Grey.

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black

ACTIVATION PLUNGER 16. Nylon plunger with rounded head adjustable with a 3 mm Allen wrench. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (°C) -35° / + 200°

FIXING TYPE 2F. With premounted screws (3,5x30 pan head (wood) or 3,5x32 (steel) countersunk nickel plated screws) or
1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws).

CERTIFICATES

WORKING CYCLES 200.000 (internal test)

ACOUSTIC INSULATION **50dB** Rw - Cert. n. PB-G03-04-en-01-PB01 - IFT Rosenheim

FIRE RESISTANCE **120 mins** - Cert. n. 20/22763-1240-1 - Applus Laboratories

SMOKE TESTED /

ACOUSTIC ALU

CE2520ACA

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,160	5,65	50	330 -> 280
430	0,208	7,09	110	430 -> 320
530	0,257	8,56	150	530 -> 380
630	0,305	10,00	150	630 -> 480
730	0,353	11,40	150	730 -> 580
830	0,401	12,88	150	830 -> 680
930	0,449	14,32	150	930 -> 780
1030	0,497	15,76	150	1030 -> 880
1130	0,545	17,20	150	1130 -> 980
1230	0,593	18,64	150	1230 -> 1080
1330	0,641	20,08	150	1330 -> 1180
1430	0,689	21,52	150	1430 -> 1280
1530	0,737	22,96	150	1530 -> 1380
1630	/	/	/	/
1730	/	/	/	/
1830	/	/	/	/

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 30 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.