

Product description

Model for magnetic latch bolt locks with basic equipment and gentle latch bolt spring.

Overview of Advantages

- Compatible with conventional magnetic latch bolt locks
- Radius keep, FaFix®, adjustable by 3 mm
- Weak latch bolt spring
- Voltage range
- Compatible with existing ProFix® 2 striking plates
- Optimal outlet slopes for gentle interaction with the latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

DIN-direction	Universal
potential	22-42 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
For magnetic latch bolt lock	Yes
Weak latch bolt spring	Yes
Noise reduction	Yes
Continuous duty	22-26 V DC
Rated resistance	200 Ohm
Current consumption 24 V AC	60 mA
	120 mA
	50 N
	200 N
Break-in resistance	3750 N
Height	66 mm
Width	20,1 mm
Depth	25,5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Suitable for fire doors	No

Article number 118TQ13- ---- B71

EAN 4042203455016

