

Product description

Model with mechanical unlocking.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Voltage range
- Compatible with current mortise locks
- Compatible with existing ProFix® 2 striking plates
- Optimal latch ramps for gentle interaction with the latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

DIN-direction	universal
	6-12 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Rated resistance	9 Ohm
Current consumption 6 V AC	550 mA
Current consumption 6 V DC (stabilised)	660 mA
Current consumption 12 V AC	1100 mA
Current consumption 12 V DC (stabilised)	1300 mA
Suitable for fire doors	No
Max. preload 12 V AC	160 N
Max. preload 6 V DC (stabilised)	10 N
Max. preload 12 V DC (stabilised)	60 N
Break-in resistance	3750 N
Height	66 mm
Width	20.1 mm
Depth	25.5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5.5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Max. preload 6 V AC	160 N
Max. latch preload DC (50% ripple) 12 V	100 N
Max. latch preload DC (50% ripple) 6 V	40 N

Article number 118E.13- - - - - D11

EAN 4042203379381

