

Product description

Model with weak keeper spring.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Weak latch bolt spring
- Voltage range
- Compatible with current mortise locks
- Compatible with ProFix® 2 strike plates
- Optimal latch ramps for gentle interaction with the latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

DIN-direction	universal
	10-24 V AC/DC
Fail-locked	Yes
Weak latch bolt spring	Yes
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Current consumption 12 V AC	250 mA
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
Load cycles for in-plant test	250000
Installation position	Vertical and horizontal
Operating temperature range	-15 °C to +40 °C
Break-in resistance	3750 N
Height	66 mm
Suitable for fire doors	No
Depth	26 mm
Latch bolt engaging depth	5.5 mm
Width	20.1 mm
FaFix® adjustment range	3 mm
Max. preload 12 V DC (stabilised)	50 N
Max. preload 24 V DC (stabilised)	200 N
Max. preload 12 V AC	200 N
Max. preload 24 V AC	> 350 N

Article number 118Q13- - - - - A71

EAN 4042203412910

