

Product description

Model with basic equipment. Also useable as a heavy-duty electric strike.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Compatible with ProFix® 2 strike plates
- Optimal latch ramps for gentle interaction with the latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Note

- Can only be used as a supplementary locking device on fire doors
- Not an authorised locking system for doors along escape and rescue routes

Technical data

| | |
|---|-------------------------|
| DIN-direction | universal |
| | 12 V DC |
| Adjustable keeper (FF, FaFix®) | Yes |
| Fail-unlocked | Yes |
| Bi-directional diode | Yes |
| Rated operating voltage tolerance range | ± 10% |
| Rated resistance | 51 Ohm |
| Current consumption 12 V DC | 235 mA |
| Break-in resistance | 9000 N |
| Height | 66 mm |
| Width | 20.1 mm |
| Depth | 26 mm |
| FaFix® adjustment range | 3 mm |
| Latch bolt engaging depth | 6 mm |
| Operating temperature range | -15 °C to +40 °C |
| Installation position | Vertical and horizontal |
| Load cycles for in-plant test | 250000 |
| Material housing | Steel |
| Latch material | Steel |
| Max. latch preload DC (stabilised) | 30 N |

| | |
|----------------|-----------------|
| Article number | 138F.13-----E91 |
| EAN | 4042203467170 |

