

Product description

Model with basic equipment.

Overview of Advantages

- Water-proof for use outdoors
- Protection rating IP54 for the electrical components
- Connecting cable 300 mm length
- Equipped with bipolar protective diodes
- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Compatible with ProFix® 2 strike plates
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Note

- Not an authorised locking system for doors along escape and rescue routes

Technical data

| | |
|------------------------------------|-------------------------|
| DIN-direction | universal |
| | 12 V DC |
| Adjustable keeper (FF, FaFix®) | Yes |
| Fail-unlocked | Yes |
| Bi-directional diode | Yes |
| Rated resistance | 51 Ohm |
| Current consumption 12 V DC | 235 mA |
| Break-in resistance | 3750 N |
| Height | 66 mm |
| Width | 20.1 mm |
| Depth | 26 mm |
| FaFix® adjustment range | 3 mm |
| Latch bolt engaging depth | 5.5 mm |
| Operating temperature range | -40 °C to +50 °C |
| Installation position | Vertical and horizontal |
| Load cycles for in-plant test | 250000 |
| Max. latch preload DC (stabilised) | 30 N |

Article number 138W.13- - - - E91

EAN 4042203634350

