


# Fast assembly concealed hinge

- Accessories
- For Sensys


## Adapter plate for parallel adapter



- For connecting parallel adapters
- Quality classification under EN 15570, Level 3
- For use in 28 or 37 mm hole line
- Can only be used with screwed on adapter
- Hole spacing 32 mm
- Oblong hole height adjustment  $\pm 3$  mm (versions for screwing on / with premounted Euro screws)
- Oblong hole height adjustment  $\pm 2$  mm (version with expanding sockets)
- Nickel plated die-cast zinc

Cup assembly	Mounting hole $\varnothing \times T$ mm	Order no. / Distance D mm			PU
		0.0	1.5	3.0	
for screw mounting with $\varnothing 4.5 \times 16$ mm flat head screws	-	<b>9 106 989</b>	<b>9 106 990</b>	<b>9 106 991</b>	50 ea.
with expanding sockets	$\varnothing 10 \times 12$	<b>9 106 983</b>	<b>9 106 984</b>	<b>9 106 985</b>	50 ea.
with premounted Euro screws	$\varnothing 5 \times 12$	<b>9 106 986</b>	<b>9 106 987</b>	<b>9 106 988</b>	50 ea.


## Parallel adapter



- For screwing onto the adapter plate
- Distances of up to 25 mm can be reached in combination with the adapter plate
- Including fixing screw
- A trial mounting is recommended
- Nickel plated die-cast zinc

Distance D mm	Order no.	PU
8.0	<b>9 072 537</b>	50 ea.
12.0	<b>9 072 538</b>	50 ea.
22.0	<b>9 072 539</b>	50 ea.

## Angle adapter for cross mounting plates



- For realizing face angle applications
- A trial mounting is recommended
- Plastic, anthracite

Angle W°	Order no.	PU
-5	<b>9 237 120</b>	50 ea.

Can only be used with LR37 cross mounting plates for screwing on, screw length is defined by the specific configuration